



THE UNITED KINGDOM VEHICLE APPROVAL AUTHORITY

COMMUNICATION CONCERNING THE ~~APPROVAL GRANTED<sup>(4)</sup>~~/ APPROVAL EXTENDED<sup>(1)</sup>/  
~~APPROVAL REFUSED<sup>(4)</sup>~~/ ~~APPROVAL WITHDRAWN<sup>(4)</sup>~~/ PRODUCTION DEFINITELY  
~~DISCONTINUED<sup>(4)</sup>~~ OF A TYPE OF MECHANICAL COUPLING DEVICE OR COMPONENT,  
PURSUANT TO REGULATION NO 55.01



Approval No: 55R-014637

Extension No: 01


1. Trade name or mark of the device or component: VBG
2. Manufacturer's name for the type of device or component: MLTD 1-2
3. Manufacturer's name and address:  
VBG GROUP AB  
Herman Kreftings gata 4  
S- 462 28 Vänersborg  
Sweden
4. If applicable, name and address of the manufacturer's representative: Not applicable
5. Alternative supplier's names or trade marks applied to the device or component: Not applicable
6. Name and address of company or body taking responsibility for the conformity of production:  
VBG GROUP TRUCK EQUIPMENT AB  
Tenggrenstorpsvägen 11  
S-462 28 Vänersborg  
Sweden
7. Submitted for approval on: As before and 29 November 2013

EAP294695

An executive agency of the Department for Transport  
July 2012 Revision 4



8. Technical service responsible for conducting approval tests: TÜV SÜD Auto Service GmbH
9. Brief description: Non-standard drawbar
- 9.1. Type and class of device or component: MLTD 1-2
- 9.2. Characteristic values:
- 9.2.1. Primary values:  
 D: 188 kN    Dc: - kN    S: - kg  
 U: - tonnes    V: - kN
- Alternative values: Not applicable  
 D: - kN    Dc: - kN    S: - kg  
 U: - tonnes    V: - kN
- 9.3. For Class A mechanical coupling devices or components, including towing brackets:
- Vehicle manufacturer's maximum permissible vehicle mass: kg Not applicable
- Distribution of maximum permissible vehicle mass between the axles: Not applicable
- Vehicle manufacturer's maximum permissible towable trailer mass: kg Not applicable
- Vehicle manufacturer's maximum permissible static mass on coupling ball: kg Not applicable
- Maximum mass of the vehicle, with bodywork, in running order, including coolant, oils, fuel, tools and spare wheel (if supplied) but not including driver: kg Not applicable
- Loading condition under which the tow ball height of a mechanical coupling device fitted to category M<sub>1</sub> vehicles is to be measured -see paragraph 2 of annex 7, appendix 1:  
 Not applicable
- 9.4. For class B coupling heads, is the coupling head intended to be fitted to an unbraked O<sub>1</sub> trailer  
 YES/NO<sup>(1)</sup> Not applicable
10. Instructions for the attachment of the coupling device or component type to the vehicle and photographs or drawings of the mounting points given by the vehicle manufacturer:  
 See manufacturer's documentation
11. Information on the fitting of any special reinforcing brackets or plates or spacing components necessary for the attachment of the coupling device or component: Not applicable
12. Additional information where the use of the coupling device or component is restricted to special types of vehicles - see annex 5, paragraph 3.4: Not applicable

13. For Class K hook type couplings, details of the drawbar eyes suitable for use with the particular hook type: Not applicable
14. Date of test report: As before and 28 January 2014
15. Number of test report: 08-00030-CX-GBM Extension 03
16. Approval mark position: Type plate on the component
17. Reason(s) for extension of approval: To cover
  - 1) Increase of D-value
  - 2) Change of name of technical service
18. Approval ~~GRANTED/EXTENDED/REFUSED/WITHDRAWN~~<sup>(1)</sup>
19. Place: BRISTOL
20. Date: 20 FEBRUARY 2014
21. Signature:  A. W. STENNING  
Head of Technical and Quality Support Group
22. The list of documents deposited with the Administration Service which has granted approval is annexed to this communication and may be obtained on request.

Any remarks: Approval to Supplement 03

(1) Strike out what does not apply.

relating to the EEC and ECE type-approval as a component of mechanical coupling devices for motor vehicles and their trailers (94/20/EC and UNECE 55-01).

0. GENERAL

0.1. Make (trade name of manufacturer): VBG

0.2. Type and commercial description(s): MLTD 1-2

versions: Drawbar equipped with 50 mm drawbar eye or  
 Drawbar equipped with 57,5 mm drawbar eye or  
 Drawbar equipped with MFC/DW or  
 Drawbar equipped with MFC/DW-H

0.5 Name and address of manufacturer: VBG GROUP AB  
 Herman Kreftings gata 4  
 S-462 28 Vänersborg  
 Sweden

0.7. Location and method of affixing of the ECE and EEC approval mark:  
 On labels mounted on the side of both legs.

0.8 Address(es) of assembly plant(s): VBG GROUP TRUCK EQUIPMENT AB  
 Tenggrenstorpsvägen 11  
 S-462 28 Vänersborg  
 Sweden

1. CONNECTIONS BETWEEN DRAWING VEHICLES AND TRAILERS AND SEMITRAILERS

1.1. Detailed technical description (including drawings and material specifications) of the type of the mechanical coupling device:

Hinged drawbar for mounting on a towed vehicle.  
 Overall dimensions: See enclosed information drawings.  
 Drawings and material specification: See enclosed list.

1.2. Class and type of coupling device(s): Class E, Non-standard drawbar.

1.3. Maximum D-value: 188 kN

Dc-value: Not applicable

1.4. Maximum vertical load S at the coupling point: Not applicable

1.5. Maximum load U at the fifth wheel coupling: Not applicable

1.6. Maximum V-value: Not applicable

1.7. Instructions for attachment of the coupling type to the vehicle, additional information regarding restrictions of use to special types of vehicles:

See enclosed mounting instructions.  
 Maximum permitted axle load of the steered axle,  $A_v = 18$  tonnes.

1.8. Information on the fitting of special towing brackets or mounting plates:  
 Not applicable

